

## 6090 Reduced Barrier Airconditioning Hose SUPERCOOL



**Hose construction:**

Seamless chloroprene inertube, covered with a nylon barrier layer and reinforced with one fabric braid. Hose has weather, oil and abrasion resistant rubber cover of butyl, which is perforated.

**Temperature range:** -40 °C to 135 °C (-40 °F to 275 °F)

**Specification:** Meets J2064 “type C class I” hose performance for R134a and R1234yf, ISO 8866-2 and Burgaflex R452 transport refrigerant specification

**Compatible with:** R134a with PAG oils, Modified PAG’s. POE van PVE lubricating oils  
R1234yf with ND-12 and SP-A2 oils  
R452 with PAG oils, Modified PAG’s. POE van PVE lubricating oils

Part no.	Hose size	Hose I.D. (min-max mm)	Hose O.D. (mm)	Working pressure (bar)	Burst pressure (bar)	Weight (Kg/m)	Bend radius (mm) (*)
6090-06	5/16"	8.1	15.2	35	140	0,13	50
6090-08	13/32"	10,7	17.8	35	140	0,18	64
6090-10	1/2"	12.9	19.9	35	140	0,19	76
6090-12	5/8"	16,1	24.1	35	120	0,34	102

Revision 09/19